

REC'D 17 DEC 2003
WIPO PCT

PCT/IB 03/05546
27.11.03
INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

Best Available Copy

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *M. C. Cooke*

Dated 12 September 2003

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

The
Patent
Office

1/77

THE PATENT OFFICE

13 DEC 2002

RULE 97
NEWPORT

The Patent Office
Cardiff Road
Newport
Gwent NP10 8QQ

request for grant of a patent
See notes on the back of this form. You can
so get an explanatory leaflet from the Patent
Office to help you fill in this form)

Your reference

PHIE020003

13 DEC 2002

Patent application number
(The Patent Office will fill in this part)

0229245.6

16DEC02 E771249-1 003008
P01/7700 0.00-0229245.6

Full name, address and postcode of the or of
each applicant (underline all surnames)

KONINKLIJKE PHILIPS ELECTRONICS N.V.
GROENEWOUDSEWEG 1
5621 BA EINDHOVEN
THE NETHERLANDS

Patents ADP Number (if you know it)

07419294001 ✓

If the applicant is a corporate body, give the
country/state of its incorporation

THE NETHERLANDS

Title of the invention

TELEVISION DISPLAY UNIT

Name of your agent (if you have one)
"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

Philips Intellectual Property and Standards
Cross Oak Lane
Redhill
Surrey RH1 5HA
08359655001 ✓

Patents ADP number (if you know it)

If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (if you know it)
the or each application number

Country

Priority Application number
(if you know it)

Date of filing
(day/month/year)

If this application is divided or otherwise
derived from an earlier UK application, give
the number and the filing date of the earlier
application

Number of earlier application

Date of filing
(day/month/year)

Is a statement of inventorship and of right to
grant of a patent required in support of this
request? (Answer "Yes" if:

YES

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an
applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	16
Claims(s)	3
Abstract	1
Drawings	2



1. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(Please specify)

I/We request the grant of a patent on the basis of this application.

Signature

Richard Turner

Date

12.12.02

Name and daytime telephone number of person to contact in the United Kingdom

01293 815492

(R. Turner)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

Write your answers in capital letters using black ink or you may type them.

If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.

If you have answered "Yes" Patents Form 7/77 will need to be filed.

Once you have filled in the form you must remember to sign and date it.

For details of the fee and ways to pay please contact the Patent Office.

DESCRIPTION

TELEVISION DISPLAY UNIT

5 The present invention relates to television display unit and methods of processing television signals.

 Picture-in-Picture (or PiP) is a feature that allows the display of a smaller second video stream or still picture sequence in a corner of the main video picture. This second picture can e.g. be used to monitor one
10 video stream while watching another.

 PiP has been possible technically since the 1980's namely even when only analogue television signals were available. Even though it has proven to be a highly desirable feature, it has never reached mainstream products due to the associated cost. In particular, in an analogue TV, an
15 expensive extra tuner, extra memory and an additional signal processing block is required to make the feature possible.

 An object of the present invention may be to provide a television display unit enabling picture-in-picture capability at lost cost.

 The present invention provides a television display unit comprising
20 a receiver for a plurality of channels of television signals, means for displaying signals of a television channel, means for inputting signals of another television channel, means for displaying one channel as a reduced image additional to the main display in the on-screen-display plane.

 In this way, PiP facility is provided with limited process capability.

25 In one form, the present invention may provide PiP with limited tuner capability.

 The television display unit may include any one or more of the
30 following features:-

- means to effect real-time decoding for displaying one channel as a rendered image in the on-screen-display plane.
- means to effect time-sharing of the signals for decoding.
- conversion means from full-colour video pictures to palette-based pictures for reduced-image display on the OSD plane.
- conversion means comprises quantisation means for the pixel values and means to add a palette entry for each palette colour not yet in the palette.
- conversion means comprises means to run length encode the pixels to produce groups of comparable value.
- conversion means comprises means to reduce the quantization level until attainment of a required colour level.
- conversion means comprises means to map the pixels to the palette colours.

The present invention also provides remote control apparatus to operate a television display unit of the present invention.

The present invention also provides a method of operating a television display unit comprising displaying signals of a television channel, inputting signals of another television channel, displaying one channel as a reduced image additional to the main display in the on-screen-display plane.

Another aspect of the present invention provides a computer program product directly loadable into the internal memory of a digital computer, comprising software code portions for performing the steps of the method of the present invention when said product is run on a computer.

Another aspect of the present invention provides a computer program for performing the steps of the method of the present invention when said product is run on a computer.

The present invention also provides a carrier, which may comprise electronic signals, for a computer program embodying the present invention.

5 The present invention also provides electronic distribution of a computer program of the invention.

In order that the invention may more readily be understood, a description is now given, by way of example only, reference being made to the accompanying drawings, in which:-

10 Figure 1 is a television display unit embodying the present invention;

Figure 2 shows stages in a conversion process.

The present invention involves a CPU on a MPEG video decoder to provide Picture-in-Picture (PiP) functionality, by decoding MPEG frames in software and rendering the decoded frame on top of the video plane.

15 The television display unit reduces the frame rate of the PIP video, while eliminating the main cost factors, namely:

- Memory: use of memory that is already available for a MPEG decoder.
- 20 • Signal processing: all signal processing is done in the main CPU which is already available. Processing is done in the background in order to avoid use of other software running on the CPU.
- 25 • Tuner: in television receivers with only one tuner, PiP is provided for a limited amount of channels, only those channels in the same transport stream (or TS) multiplex. Television receivers with PVR functionality (i.e. with hard-drive) use the PVR as a second video source, thus allowing for PiP of PVR/TV content. Television receivers with a broadband modem can use streaming video streams as additional sources. Finally,
30 television receivers with more than one tuner allow for unlimited TV PiP functionality.

DVB Video distribution uses a large number of separate frequencies (transponders) to send digital streams down from a satellite. On one such frequency, a limited amount of bandwidth is available (typically 30-60 Megabit per second). The stream that is send on one frequency is called a
5 transport stream (TS) and contains a multiplex of a number of programs, typically 4-10 programs (e.g. BBC1, BBC2, etc). Some broadcasters buy a transponder in a satellite and use the one TS to send all their programs out in the same TS on the same frequency.

In a set-top box with only one tuner, only one TS can be received at
10 a time (to go to another one the frequency of the tuner needs to change). Thus if a person is watching a certain program on the main screen in a single tuner box, there is only access to video information for another program if this program is broadcast in the same TS. If one wants PiP for a program in a different TS, it is necessary to have a box with 2 tuners.

15 The conversion operation from full-colour video to palette-based video involves some detailed processing. A first implementation of this processing is a simple quantisation of the pixel YUV values by making the "least significant bits" zero (i.e. truncation) e.g. DIV by 16 gives $Y=45 = 0b00101101$ becomes $Y=32 = 0b00100000$.

20 The palette is built by progressing through the pixels and adding a palette entry for each pixel color that is not yet in the palette.

The quantization limits the total amount of different colors in the total picture, so that most of the pictures have less than 256 different colors. In the initial implementation, if a picture has more than 256 colors, it
25 is not displayed and the next one is taken.

A further-refined implementation as shown in Figure 2 consists of the following steps:

1. Quantization as above, operation 30. Then there is an initial performing of a very rough quantization (e.g DIV 64), to guarantee that a
30 palette with <256 colors is found;

2. Run-length-encoding of the quantized pixels to form pixel-runs, operation 31. Because there are less pixel-runs (groups of pixels with the same value) than pixels, this will speed up the rest of the processing;

3. Building an initial palette, operation 32;

5 4. Determining for which of the colors in the "rough" palette after step 1 above the total quantization error for all pixels that use that particular palette entry is the largest, operation 33. So, calculations are made for each of the colors i in the palette $ERR[i] = \text{SUM}(\text{palette_color}[i] - \text{color}[j])$, where j runs over all the pixels that use palette entry i . For the
10 color in the palette which has the largest total error, the quantization level is reduced e.g. to DIV 32.

5. Building a palette, operation 34.

6. Steps 4 and 5 are repeated until 256 colors is reached, operation
35.

15 7. Finally, the pixels are mapped to the palette colors (bitmapping) so that pixel values are replaced by palette indices, operation 36. Because the palette was ordered in the previous steps, it is feasible to use a fast binary search to find what palette entry the pixel is mapped to. The palette is ordered in Y, U, V, e.g. color 100 90 70 is larger than 90 100 100
20 because the Y value is larger, so it is higher up in the palette.

It is also possible to do the pixel mapping right after quantization, after steps 2 and after 4 (in the refinement loop).

It is necessary to make optimal use of the spatial correlation between pixels. So, if a pixel has to be mapped, it is likely it has the same
25 color as its predecessor, and therefore doing a full palette search for an individual pixel is on average not efficient. It is beneficial to run-length encode the picture before processing so that one can perform operations for groups of pixels. This means building up an array with (runlength, pixel_value) pairs starting with a simple horizontal line-based scan.

30 The situation can be simplified by defining the ultimate goal as obtaining a minimum for the sum of color-errors over the picture. The most

fast error measure is probably the 3D sum of absolute differences, so
GOAL: Minimize $\text{Sum}(|Y_n^* - Y_n| + |V_n^* - V_n| + |U_n^* - U_n|)$ with $0 < n < N$ with $*$
denoting approximation and N the number of pixels in the picture.

5 It is possible to use a hierarchical approach, starting with
quantization by 32 and building an initial palette with binary search used to
avoid duplication in the palette. Assume this palette will never overflow. An
initial bitmap is generated using these rough colors, which can be done
fast because the exact color is known is in the palette.

10 When building up the palette, the total error is maintained for each
of the colors in the palette by calculating the color error for each and every
pixel and adding it to the total of the particular color. This total error is the
sum of the errors of all the pixels (or better: runlength groups of pixels) that
have been assigned a particular color.

15 One can start refining the colors, beginning with the entry in the
palette for which the total error is largest. For this palette entry, new
mapping is done with quantization factor of 16 (so possible up to 8 colors
come out of the 1 original rough color), and the error totals for the new
colors are updated. This step includes updating the corresponding entries
in the bitmap.

20 This operation is repeated (for the area with the largest error) until
the palette is full, going to $Q=8$ if a color with $Q=16$ becomes the worst.

Steps that merge colors with a very small error back to a rougher
color may be added in order to prevent that a few odd pixels take up a
precious color (e.g. only accepting 64 colors in the first $Q=32$ step).

25 Data compression is the reduction of redundancy in data
representation, carried out for decreasing data storage requirements and
data communication costs. A typical video codec system is presented in
Figure 1. The lossy source coder performs filtering, transformation (such
as Discrete Cosine Transform (DCT), sub-band decomposition, or
30 differential pulse-code modulation), quantization, etc. The output of the
source coder still exhibits various kinds of statistical dependencies. The

(lossless) entropy coder exploits the statistical properties of data and removes the remaining redundancy after the lossy coding.

In MPEG, the DCT is used as a lossy coding technique. The DCT algorithm processes the video data in blocks of 8 8, decomposing each block into a weighted sum of 64 spatial frequencies. At the output of DCT, the data is also organized in 8 8 blocks of coefficients, each coefficient representing the contribution of a spatial frequency for the block being analyzed.

Following a zig-zag path, the matrix is transformed into a vector of coefficients, and further compressed by an entropy coder which consists of two major parts: Run-Length Coder (RLC) and Variable-Length Coder (VLC). The RLC represents consecutive zeros by their run lengths; thus the number of samples is reduced. The RLC output data are composite words, also referred to as source symbols, which describe pairs of zero-run lengths and values of quantized DCT coefficients. When all the remaining coefficients in a vector are zero, they are all coded by the special symbol end-of-block.

Variable length coding, also known as Huffman coding, is a mapping process between source symbols and variable length codewords. The variable length coder assigns shorter codewords to frequently occurring source symbols, and vice versa, so that the average bit rate is reduced. In order to achieve maximum compression, the coded data is sent through a continuous stream of bits with no specific guard bit assigned to separate between two consecutive symbols. As a result, decoding procedure must recognize the code length as well as the symbol itself.

In the present system, the MPEG encoder in the headend has used VLC to code symbols into a string of variable length bit-strings (e.g. symbols can be 2,3,4,5,16 bits long and are not byte aligned in the final stream). Even though they are not byte aligned, one can still find out where a new symbol starts because each symbol is unique.

In the MPEG decoder, it is necessary to read the stream bit-by-bit and derive the original symbols (run-length pairs) from it. This is called variable length decoding (VLD).

In order to achieve an acceptable performance (in terms of frames/MIPS), the microdecoder is specifically optimised for the PiP task. More specifically, it only decodes a few coefficients per DCT block, resulting in a reduced resolution for the output picture. It decodes I frames and only 3 out of the total of 64 coefficients in a DCT block, giving a factor 4 of reduction in resolution in both horizontal and vertical direction. There is no fundamental restriction for doing just I frames and the number of used coefficients/resolution can be changed according to the constraints.

The decoder performs the following actions:

1. It sets up demultiplexing to write the secondary video stream into a memory buffer.
2. It waits until there is an I frame in the buffer (a frame interrupt is used to signal the arrival of a new frame, the software in the decoder checks the frame header to determine if it is an I frame, otherwise it skips it).
3. It decodes the headers of the I frame until the first DCT block is found.
4. In the DCT block, a VLC decode for the first 3 coefficients is performed.
5. An inverse DCT is performed to obtain 4 pixel values per DCT block (which is very simple for only 3 coefficients).
6. A VLD operation must be performed for all coefficients that follow the third coefficient in the particular DCT block (even though they are not used in the IDCT and their value does not influence the pixel values), because of the way that MPEG works since the start of the next DCT block is not byte-aligned in any way. The only way to find the start of the next DCT block is to read away all VLD words of the previous DCT block.

7. This procedure is repeated for all DCT blocks in the frame, the resulting pixel values are written into a frame buffer.

8. If necessary, a filtering operation (post processing) is used on the picture in the frame buffer, in order to improve visibility of the PiP picture at normal viewing distances.

9. The picture in the resulting frame buffer is rendered onto the OSD plane (or Video/Still plane depending on the decoder).

For the VLD performed in step 6 above (which is the most processing-intensive operation in the entire decode process), the result of this VLD is not essential (it only being necessary to read the bits away to get to the next VLD word) to develop a faster VLD function. The speed improvement is obtained by reading away the bits in the VLD word as soon as the size of this VLD word is known, and omit looking up the runlength/value pair in a VLD table. This step is important for achieving a software decode performance to enable implementation at low cost.

Post processing

Because the PiP picture has a reduced resolution and uses a lower frame-rate, sometimes it may be difficult to see what the image content actually represents. This is partly caused by the fact that the original video content was intended for a viewing distance of 3-5 times the image size.

In order to improve the visibility, a post-processing filter is used to adjust the contrast and brightness of the PiP picture, and thereby help recognition. In pictures with large areas that differ in intensity from each other, increasing the contrast can lead to unwanted effects. It is therefore desirable to adjust contrast/brightness differently on an image-segment by image-segment basis. For example, for a picture with a beach, a sea and a blue sky, there could be a different contrast/brightness adjustment for beach, sea and sky.

Rendering

The PiP image is displayed on top of the normal video in the OSD (i.e. On Screen Display) plane.

5 For the most popular decoder chip-sets and also for some other chip-sets, the order of the display planes is fixed and higher image planes conceal underlying planes. For such chip-sets, the still-picture plane is behind the video plane and the video plane is behind the OSD plane.

10 The OSD plane is used for display of the PiP which requires the true-colour PiP Image (YUV) to be converted into a bitmap and mapped onto the available OSD palette (256 colours for the most popular chips). In fact, for acceptable picture quality, the palette must be selected and optimised on a picture-by-picture basis depending on the different colours in the picture. A few colours in the palette can be reserved to allow for
15 specific OSD graphics to be displayed in another part of the screen while showing PiP.

The television receiver includes the following features:-

1. Decoding individual frames originating from a live video feed in a MPEG decoder, while simultaneously decoding a second stream in the
20 hardware decoder.

2. Emulating a multi-screen decoder by decoding frames from a number of different streams, by decoding a single frame from one stream, then one from another stream, etc, then display the frames.

3. The optimised VLD operation for reading-away unused VLD
25 words, in order to get to the start of the next DCT block.

4. The use of the OSD plane for showing PiP and the selection of the OSD palette depending on the image contents.

5. The use of a PVR as a second source with the PiP facility showing PVR content while watching TB or showing live TB while watching
30 PVR.

6. The use of streaming video over a broadband connection as a second source.

7. Post processing to optimise the recognition of the content of the PiP pictures at normal viewing distances.

5 8. The generation of a Mosaic for an EPG by TDMA processing several channels.

Feature 5 may allow a viewer to watch a time-delayed version of a TV program coming from the PVR, while monitoring the live feed in a PiP window. Thus for example a viewer may start to watch a soccer match 30
10 minutes late, may catch up by fast forwarding selected parts of the beginning of the match, but in the meantime monitor the live match in the PiP in order to see whether there are any new goals).

When a break for advertisements occurs during the television program, PiP is often used by viewers for monitoring (in the PiP window)
15 the main program while the other TV channels for more interesting content. This could mean that offering PiP actually may result in a reduction of the exposure of viewers to commercials, which is bad for the service provider.

In the present invention, by only providing PiP for specified
20 channels, for example those restricted to one or more service provider, viewing behaviour can be limited or restricted so that only switching between the specified channels (e.g. those of the service provider) is encouraged.

This operates as follows:

- 25 1. A viewer is watching a movie on SKY Movies.
 2. At a certain moment, there is a commercial break.
 3. The viewer switches away from SKY Movies, but keeps SKY Movies in a PiP window in order to monitor the progress of the commercial block while zapping.
30 4 When the viewer switches to a program in the SKY bouquet, the PiP window is present.

5. However, when the viewer switches away to a free-to-air channel, the PiP window disappears.

6. Since he is interested in watching the rest of the movie, this encourages the viewer to watch only other SKY channels while waiting for the commercial block on SKY Movies to end.

7. Because of this, the risk of the viewer permanently switching away to a channel owned by another service provider is reduced.

In a low-cost box with a single tuner and no PVR, PiP is only available for channels in the same TS multiplex. If all programs in the multiplex are owned by the same service provider, then the "loyalty PiP" strategy as outlined above is a useful feature that results directly from the single-tuner restriction.

With reference to the specific implementation described in relation to the Figures, Figure 1 shows a television receiver 1 having input circuitry 2 including tuners 3 and 4, hard disk unit HDD 5, all of which can input to demultiplex unit 6 and to the television monitor 7.

The MicroDecoder unit 8 receives real-time MPEG2 video data from the demux 6 or MDD units. It decodes the MPEG2 video stream, performs post-processing to optimize the picture quality and outputs the video pictures to a TV or to a companion device via a wireless link.

For display on a TV, the video data is rendered onto an OSD plane. Before output to a companion device 9 via a wireless link 10, the video data is re-encoded using a proprietary compression scheme in order to minimise the data rate on the wireless link and maintain the picture quality.

Operation of the PiP facility is by use of a remote control unit 11 with appropriate command signals for microdecoder unit 8 and ancillary equipment.

The microdecoder unit 8 is a MPEG2 video decoder with software capability, and frame-rate and resolution are targeted at monitoring of secondary video streams. The memory footprint and processing load are highly optimised for deployment in low-cost set-top boxes. The decoder 8

has flexible real-time requirements in order to allow for easy integration with existing STB software and comes with associated chip-specific MPEG frame-capture and rendering modules.

5 The decoder 8 enables monitoring of secondary live video channels e.g. for monitoring main channel when switching during a commercial, or monitoring major events other channels, allowing for second channel monitoring, multi channel monitoring or Mosaicing for advanced channel surfing.

10 It allows monitoring of secondary video streams while using a PVR, e.g. for monitoring a channel that is being recorded while watching another channel. Monitoring the live video feed while watching a time shifted version, browsing PVR content while watching a live video channel, building a mosaic for browsing PVR content.

15 Furthermore, it enables off screen video monitoring using a TV companion device.

The MicroDecoder unit 8 fully complies with the MPEG2 video standard including different image sizes and frame rates, field+frame coding, both can patterns, different quantization matrices, yet it was designed for seamless integration with existing STB software.

20 This means it provides, low processor load, flexible real-time requirements, can run in the background, so it won't disturb other tasks, small ROM footprint, small RAM footprint.

25 The television receiver includes acquisition and rendering modules for specific decoder architectures, or a decoding core, optimised in assembly for a specific processor, or integration of the MicroDecoder with existing STB SW "set-top box" software, for systems for several middleware standards like OpenTV, NDS, Microsoft TV and MediaHighway.

30 In an implementation, one can switch between each of the, for example, 20 channels, but the PiP facility is not available for channel providers other than that of the principal channel currently being viewed.


In this way, the viewer is encouraged to check only those channels associated with the same channel provider, in this instance C2 to C4 because he still wants to monitor C1.

For example, consider Sky Sports. Sky has a single tuner box with ST chip. Sky could upgrade the SW in their boxes (remotely) to offer a feature that allows a viewer to watch one Sky Sports channel (say Sky Sports 1 or SP1) while monitoring any of the 2 other Sky Sports channels in a PiP window.

User scenario: While watching SP1, the user presses the PiP button on the remote and the SP2 and SP3 show up in separate PiP windows. Repeated presses on the PiP window toggles between

SP2 PiP only,
SP3 PiP only,
No PiP,
SP2+SP3 PiP.

While PiP is on, channel up/down only changes between SP1, 2, and 3. In this mode, the PiP version of the channel that is watched on the main screen disappears or is replaced e.g. as follows:-



Note that, once PiP is switched off (by pressing "PiP" repeatedly), channel up/down allows access to all Sky channels again.

The steps of implementing another embodiment are as follows:-

1. A person is watching a program on Channel 1 (hereinafter known
5 as C1).

2. An advertisement break or the programme end occurs.

3. He reduces C1 to PiP.

4. He puts the main image to C2, or the step of 3 above
automatically replaces C1 with another channel e.g. C2.

10 5. He switches the main image from C2 to C3.

6. He switches the main image from C3 to C4.

7. He switches the main image from C4 to C1 (a feature of the
invention being that there are no further channels to choose from, albeit
the television receives 20 channels in total, but all the others are from
15 different channel providers from that of C1 to C4).

In a variant, he presses a button for "auto switch" which replaces
step 3 above by reducing C1 to PiP and then automatically switching
between C2 to C4 continuously, stopping at each for 5 seconds. The
sequence is stopped by pressing the button again. Alternatively, the
20 switching occurs while the button is depressed and stops once the button
is released.

The chip looks for an action being a reduction to PiP followed within
a specified period, for example 5 seconds, by at least one switching. In a
variant, the chip detects that C1 is in an ad break or a programme break.
25 In another variant, there is provided a statistical analysis, for example, if
the viewer watches C1 continuously for 25 minutes, one can deduce that
there is something of interest, and so a channel change after that period of
time would probably be during a commercial break, or just a switch to
check for anything else. If the user is switching fast (e.g. there being less
30 than 10 seconds between channel changes), the user is actually checking
on what is presently on all the other channels.

Further developments are as follows:-

1. Using a plurality of PiP images of alternative channels provided by the same channel provider. C1 can either be kept as the main image, or as one of the PiPs while highlighted in some way, for example with a white boarder.

2. Auto-switching between C2 to C4 with e.g. 5 second periods for channel while displayed. This auto-switching can be used in any version of the invention to provide switching between the channels of the same channel provider.

A multi-PiP user scenario for the original case of unlimited channel changes could e.g be:

A commercial break starts while watching a soccer match on Sky Sports 1.

The user presses the PiP button once to indicate that he wants to keep monitoring this channel. The main screen keeps displaying SP1 and there is no PiP picture yet.

The user changes channels and the SP1 PiP appears on those channels that are in the same multiplex.

Pressing PiP while a PiP window is present on the screen (e.g. in SP2) will disable the active PiP and remove the window.

Pressing PiP on any channel that doesn't show the PiP window (channel in different multiplex or PiP disabled) will disable the previous PiP if required and select that channel for PiP.

CLAIMS

1. A television display unit comprising a receiver for a plurality of channels of television signals,

5 means for displaying signals of a television channel,

means for inputting signals of another television channel,

means for displaying one channel as a reduced image additional to the main display in the on-screen-display plane.

10 2. A unit according to Claim 1 comprising means to effect real-time decoding for displaying one channel as a rendered image in the on-screen-display plane.

15 3. A unit according to Claim 2 comprising means to effect time-sharing of the signals for decoding.

4. A unit according to Claim 2 or 3 comprising conversion means from full-colour video pictures to palette-based pictures for reduced-image display on the OSD plane.

20

5. A unit according to Claim 4 wherein the conversion means comprises quantization means for the pixel values and means to add a palette entry for each palette colour not yet in the palette.

25 6. A unit according to Claim 4 or 5 wherein the conversion means comprises means to run length encode the pixels to produce groups of comparable value.

30 7. A unit according to Claim 6 wherein the conversion means comprises means to reduce the quantization level until attainment of a required colour level.

8. A unit according to Claim 6 wherein the conversion means comprises means to map the pixels to the palette colours.

5 9. A television display unit substantially as hereinbefore described with reference to and/or as illustrated in any one or more of the Figures of the accompanying drawings.

10 10. A method of operating a television display unit for a plurality of channels of television signals, the method comprising displaying signals of a television channel, inputting signals of another television channel, displaying one channel as a reduced image additional to the main display in the on-screen-display plane.

15 11. A method according to Claim 10 comprising effecting real-time decoding for displaying one channel as a reduced image in the on-screen-display plane.

20 12. A method according to Claim 10 or 11 comprising effecting time-sharing of the signals for decoding.

13. A method according to Claim 11 or 12 comprising converting from full-colour video pictures to palette-based pictures for reduced-image display on the OSD plane.

25 14. A method according to Claim 13 wherein the converting step comprises quantizing the pixel values and adding a palette entry for each palette colour not yet in the palette.

15. A method according to Claim 13 or 14 wherein the converting step comprises run length encoding of the pixels to produce groups of comparable value.

5 16. A method according to Claim 15 wherein the converting step comprises reducing the quantization level until attainment of a required colour level.

10 17. A method according to Claim 15 wherein the converting step comprises mapping the pixels to the palette colours.

18. A method of operating a television display unit substantially as hereinbefore described with reference to and/or as illustrated in any one or more of the Figures of the accompanying drawings.

15 19. A computer program product directly loadable into the internal memory of a digital computer, comprising software code portions for performing the steps of any one or more of Claims 10 to 18 when said product is run on a computer.

ABSTRACT

TELEVISION DISPLAY UNIT

5 Television receiver 1 has input circuitry 2 including tuners 3 and 4,
hard disk unit HDD 5, all of which can input to demultiplex unit 6 and to the
television monitor 7. A Picture-in-Picture capability is provided by palette-
processing conversion and display on the OSD plane.

[Figure 1]

10

1/2




Figure 1

2/2




Fig 2

PCT Application

IB0305546



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.